

INDICATORS MD22

DATA SHEET

no: KK-W_MD22



Signal indicators constitute a special type of signal lamps. Luminous elements are based on LEDs, which feature high durability and low energy consumption. In comparison to basic lamps, indicators differ by using several LEDs that are illuminated in groups and produce certain signs, as adopted in electrical engineering and automatics. In addition, the use of an all-purpose current stabilization module for LEDs makes it possible for indicators to work under any voltage within the 24-230V AC/DC.

All signal indicators can be applied in difficult industrial conditions.

Bodies of the MD22 indicators are made of plastic. The glass cover is made of transparent polycarbonate, which is a material resistant to mechanical impacts and flame retardant. The indicators are built as monoblocks.

The MD22 indicators are intended for building in standardized $\varnothing 22.5$ mm holes – drilled in various types of control and signal equipment, or directly into bodies of machines and equipment.

TECHNICAL DATA:

Parameter	Value
Insulation rated voltage U_i	250V
Rated voltage U_e	24-230V AC/DC
Type of luminous element	LED
IP for over-desk part IP for under-desk part	IP 66/67 IP 20
Cross-sections of terminals	1x LY 0,34 - 0,75 mm ² 1x DY 0,34 - 1 mm ²
Maximum thickness of desk	6 mm
Working temperature	N/2 -15...+30°C W/3 -30...+50°C

The product conforms to the following standard PN-EN 60947-5-1.

POSITION INDICATORS

They are used in automatic systems and power engineering systems for commercial applications, and particularly for signaling positions of contacts in switches, disconnecting switches, etc., in synoptic boards of hydraulic and pneumatic systems, and of steam networks, to signal positions of valves or bolts. The luminous element in a position indicator is comprised of 10 LEDs, arranged in the shape of two perpendicular beams. Depending on the colour of LEDs, the indicators are produced in a number of versions.

	Designation	Colour	Weight [g]
	MD22WP cz MD22WP gz MD22WP cg MD22WP g MD22WP z MD22WP c	red-green yellow-green red-yellow yellow green red	22

EARTHING INDICATORS

They can be used to signal the status of an earthing switch and to indicate, whether a particular electric circuit is earthed. Yellow LEDs are arranged in such way that they make the symbol of earthing.

	Designation	Colour	Weight [g]
	MD22WU g MD22WU z MD22WU c	Yellow green red	23

SWITCH POSITION INDICATORS

They are used to signal the status of position for switches, cut off switches, disconnecting switches, etc. The indicator has a masking plate under the transparent glass cover. The plate contains a conventional symbol of the indicator's contact and three LEDs, each in different colour.

	Designation	Colour	Weight [g]
	MD22WPW	yellow-green-red	23

DIMENSIONS

